



S205 Skid Steer Loader



The turbo-charged Bobcat S205 deliver Great Performance, Vertical-path lift arms deliver More lift capacity and More lift height and reach for truck loading. Powerful diesel engines produce plenty of traction and breakout force for excavating and handling large loads. Also with a powerful hydraulic pump for efficient attachment performance.

Specifications

Performance

Rated Operating Capacity¹
ROC with Optional Counterweight
Tipping Load
Hydraulic Pump Capacity
High Flow Option
Travel Speed
Operating Weight

S205

2050 lb. (930 kg)
2150 lb. (977 kg)
4100 lb. (1864 kg)
16.3 GPM (62 L/min.)
25.5 GPM (97 L/min.)
7.0 MPH (11,3 km/hr.)
6242 lb. (2831 kg)

Dimensions

Length (with bucket)
Width (with bucket)
Height
Height to Bucket Pin

130.3 in. (3309 mm)
68.0 in. (1727 mm)
76.3 in. (1938 mm)
118.2 in. (3002 mm)

Engine

Make/Model
Fuel/Cooling
Cylinders
SAE NET HP/Displacement
Fuel Tank Capacity

Kubota/V2403 M-DI-T
Diesel/Liquid
4
61/148.5 in.³
24 gal. (90,8 L)

Operation

Steering and Drive

Forward, reverse, travel speed and steering controlled by two hand levers.

Hydraulics

Raise/lower lift arms and dump/rollback bucket controlled by two foot pedals or optional hand controls.

Transmission

Hydrostatic, four-wheel drive.

Standard Features

| | |
|---|---------------------------|
| Adjustable Cushion Seat | Front & Rear Lights |
| Automatically Activated Glow Plugs | Lift Arm Support |
| Bobcat Interlock Control System (BICS™) | Gauges/Warning Lights |
| Bob-Tach | Operator Cab |
| Deluxe Cab | Parking Brake |
| Dual Path | Seat Bar |
| Cooling System | Seat Belt |
| Engine/Hydraulic Shutdown | Tires: 31.5 x 13-16.5 |
| Front Auxiliary Hydraulics | Turbo-Charger |
| | (Approved Spark Arrestor) |

- "A" 10 - 16.5 TIRES - 66.0" (1676 mm) or 60.0" (1524 mm)
31.5 x 13 - 16.5 TIRES - 66.0" (1676 mm)
- "B" 10 - 16.5 TIRES - 56.4" (1433 mm) or 48.5" (1232 mm)
31.5 x 13 - 16.5 TIRES - 54.2" (1377 mm)
- "C" 62 in. BUCKET WIDTH - 62.0" (1575 mm)
68 in. BUCKET WIDTH - 68.0" (1727 mm)
74 in. BUCKET WIDTH - 74.0" (1880 mm)

Dimensions:

